

# Verlegeanleitung



megaloc Fliese ohne integrierte Trittschalldämmung

<p>1</p> <p>18-23°C 64-73°F</p> <p>48h</p>	<p>2</p>	<p>3</p> <p>DIN 18365, EN 1264 CA 0,3 CM % CT 1,8 CM %</p>	<p>4</p> <p>max. 2 mm / 1 m 5/64 inch / 1 inch</p>
<p>5</p> <p>max. 1,5 mm min. 150 kPa</p>	<p>6</p> <p>max. 1,5 mm / 7/64 inch min. 150 kPa</p>	<p>7</p> <p>18-23°C 64-73°F</p>	<p>8</p> <p>10 mm 3/8 inch</p> <p>&gt; 50 cm 20 inch</p> <p>&gt; 20 cm 8 inch</p>
<p>9</p>	<p>10</p> <p>max. 12 m max. 39 feet</p> <p>max. 12 m max. 39 feet</p>	<p>11</p> <p>max. 29°C 84°F</p>	<p>12</p> <p>10 mm 3/8 inch</p> <p>10 mm 3/8 inch</p>
<p>13</p>	<p>14</p> <p>max. 1 mm 3/64 inch</p> <p>max. 8 mm 5/16 inch</p>		
<p>15</p> <p>min. 10 cm / 4 inch</p> <p>90°</p> <p>min. 10 cm / 4 inch</p>	<p>16</p> <p>10 mm 3/8 inch</p>	<p>17</p>	<p>18</p> <p>10 mm 3/8 inch</p> <p>min. 20 cm / 8 inch</p>
<p>19</p>	<p>20</p> <p>10 mm 3/8 inch</p> <p>min. 20 cm / 8 inch</p>		
<p>21</p>	<p>22</p>		
<p>23</p>	<p>24</p>	<p>25</p>	<p>26</p>
<p>27</p>	<p>28</p>	<p>29</p>	<p>Written Installation Instructions – Professional Tips – Certificates</p>